























|   |   |  |  |
|---|---|--|--|
|    | <p>Model: CL-L0001<br/>                     Name: L Type 2 Pins Connectors<br/>                     Fireproof:UL94-V0<br/>                     Current Max:4A<br/>                     Materials: PA66+Copper<br/>                     Applications: L Right Angle Connecting 2 Strips<br/>                     Width: 8mm<br/>                     CCT: Single color<br/>                     FPCB: Bareboard FPCB</p> |    | <p>Model: CL-L0002<br/>                     Name: L Type 4 Pins Connectors<br/>                     Fireproof:UL94-V0<br/>                     Current Max:4A<br/>                     Materials: PA66+Copper<br/>                     Applications: L Right Angle Connecting 2 Strips<br/>                     Width:10mm<br/>                     CCT: RGB<br/>                     FPCB: Bareboard FPCB</p>                 |
|    | <p>Model: CL-L0003<br/>                     Name: L Type 5 Pins Connectors<br/>                     Fireproof:UL94-V0<br/>                     Current Max:4A<br/>                     Materials: PA66+Copper<br/>                     Applications: L Right Angle Connecting 2 Strips<br/>                     Width:12mm<br/>                     CCT: RGB+W<br/>                     FPCB: Bareboard FPCB</p>        |    | <p>Model: CL-L0004<br/>                     Name: T Type 2 Pins Connectors<br/>                     Fireproof:UL94-V0<br/>                     Current Max:4A<br/>                     Materials: PA66+Copper<br/>                     Applications: T Type Connecting 3 Strips<br/>                     Width: 8mm<br/>                     CCT: Single color white<br/>                     FPCB: Bareboard FPCB</p>         |
|   | <p>Model: CL-L0005<br/>                     Name: T Type 4 Pins Connectors<br/>                     Fireproof:UL94-V0<br/>                     Current Max:4A<br/>                     Materials: PA66+Copper<br/>                     Applications: T Type Connecting 3 Strips<br/>                     Width:10mm<br/>                     CCT: RGB<br/>                     FPCB: Bareboard FPCB</p>                 |   | <p>Model: CL-L0006<br/>                     Name: Cross Type 2 Pins Connectors<br/>                     Fireproof:UL94-V0<br/>                     Current Max:4A<br/>                     Materials: PA66+Copper<br/>                     Applications: Cross Type Connecting 5 Strips<br/>                     Width: 8mm<br/>                     CCT: Single color white<br/>                     FPCB: Bareboard FPCB</p> |
|  | <p>Model: CL-L0007<br/>                     Name: Cross Type 4 Pins Connectors<br/>                     Fireproof:UL94-V0<br/>                     Current Max:4A<br/>                     Materials: PA66+Copper<br/>                     Applications: + Cross Type Connecting 5 Strips<br/>                     Width:10mm<br/>                     CCT: RGB<br/>                     FPCB: Bareboard FPCB</p>       |  | <p>Model: CL-L0008<br/>                     Name: Connectors<br/>                     Fireproof: /<br/>                     Current Max: /<br/>                     Materials: /<br/>                     Applications: L Right Angle Connecting 2 Strips<br/>                     Width:10mm<br/>                     CCT: RGB<br/>                     FPCB: Dropping Glue/IP65</p>  |
|  | <p>Model: CL-L0009<br/>                     Name: Connectors<br/>                     Fireproof: /<br/>                     Current Max: /<br/>                     Materials: /<br/>                     Applications: T Type Connecting 3 Strips<br/>                     Width:10mm<br/>                     CCT: RGB<br/>                     FPCB: Dropping Glue/IP65</p>  |  | <p>Model: CL-L0010<br/>                     Name: Connectors<br/>                     Fireproof: /<br/>                     Current Max: /<br/>                     Materials: /<br/>                     Applications: L Right Angle Connecting 2 Strips<br/>                     Width:12mm<br/>                     CCT: RGB+W<br/>                     FPCB: Dropping Glue/IP65</p>  |
|  | <p>Model: CL-L0011<br/>                     Name: Connectors<br/>                     Fireproof: /<br/>                     Current Max: /<br/>                     Materials: /<br/>                     Applications: T Type Connecting 3 Strips<br/>                     Width:12mm<br/>                     CCT: RGB+W<br/>                     FPCB: Dropping Glue/IP65</p>  |  | <p>Model: CL-L0014<br/>                     Name: L Type 4 Pins Connectors<br/>                     Fireproof: /<br/>                     Current Max: /<br/>                     Materials: /<br/>                     Applications: L Right Angle Connecting 2 Strips<br/>                     Width:10mm<br/>                     CCT: RGB<br/>                     FPCB: Dropping Glue/IP65/Bareboard FPCB</p>             |




|   |  |  |   |
|---|--|--|---|
|    | <p>Model: CL-L0027<br/>Name: Connectors<br/>Fireproof: /<br/>Current Max: /<br/>Materials: PBT+Copper<br/>Applications: Pin-to-pin connections for 2 strip light<br/>Width:10mm/12mm<br/>CCT: RGB</p>  |    | <p>Model: CL-L0028<br/>Name: Connectors<br/>Fireproof: /<br/>Current Max: /<br/>Materials: PBT+Copper<br/>Applications: Welding on Solder joint on FPCB<br/>Width:10mm/12mm<br/>CCT: RGB+W<br/>FPCB: NO Waterproof</p>  |
|    | <p>Model: CL-L0029<br/>Name: Connectors<br/>Fireproof: /<br/>Current Max: /<br/>Materials: PBT+Copper<br/>Applications: Pin-to-pin connections for 2 strip light<br/>Width:10mm/12mm<br/>CCT: RGB+W<br/>FPCB: NO Waterproof</p>  |    | <p>Model: CL-L0032<br/>Name: Bareboard FPCB connectors<br/>Fireproof: /<br/>Current Max: /<br/>Materials: /<br/>Applications: Fast Wire connected with strip light<br/>Width:10mm<br/>CCT: Single color<br/>FPCB: NO Waterproof</p>   |
|   | <p>Model: CL-L0033<br/>Name: Bareboard FPCB connectors<br/>Fireproof: /<br/>Current Max: /<br/>Materials: /<br/>Applications: Fast connection between 2 strip light<br/>Width:10mm<br/>CCT: Single color<br/>FPCB: NO Waterproof</p>   |   | <p>Model: CL-L0034<br/>Name: Bareboard FPCB connectors<br/>Fireproof: /<br/>Current Max: /<br/>Materials: /<br/>Applications: Fast Wire connected with strip light<br/>Width:10mm<br/>CCT: Double Color<br/>FPCB: NO Waterproof</p>   |
|  | <p>Model: CL-L0035<br/>Name: Bareboard FPCB connectors<br/>Fireproof: /<br/>Current Max: /<br/>Materials: /<br/>Applications: Fast connection between 2 strip light<br/>Width:10mm<br/>CCT: Double Color<br/>FPCB: NO Waterproof</p>   |  | <p>Model: CL-L0036<br/>Name: I type Single line wire-skin peeling free connectors<br/>Fireproof: UL94-V0<br/>Current Max: 5A<br/>Materials: PC+Copper<br/>Applications: 2 wires Direct connection<br/>Functions: Free wire soldering and wire skin peeling<br/>Wire: 18-22AWG ( Wire Size )</p>   |
|   | <p>Model: CL-L0037<br/>Name: I type Double lines wire-skin peeling free connectors<br/>Fireproof:UL94-V0<br/>Current Max:5A<br/>Materials: PC+Copper<br/>Applications: 4 wires Direct connection<br/>Functions: Free wire soldering and wire skin peeling<br/>Wire: 18-22AWG ( Wire Size )</p> |  | <p>Model: CL-L0038<br/>Name: T type Single line wire-skin peeling free connectors<br/>Fireproof:UL94-V0<br/>Current Max:5A<br/>Materials: PC+Copper<br/>Applications: T types connector for 2 wires<br/>Functions: Free wire soldering and wire skin peeling<br/>Wire: 18-22AWG ( Wire Size )</p> |
|   | <p>Model: CL-L0039<br/>Name: T type Double lines wire-skin peeling free connectors<br/>Fireproof:UL94-V0<br/>Current Max:5A<br/>Materials: PC+Copper<br/>Name: T type Four lines connection<br/>Functions: Free wire soldering and wire skin peeling<br/>Wire: 18-22AWG ( Wire Size )</p>      |  | <p>Model: CL-L0040<br/>Name: Black Transparent wire-skin peeling free connectors<br/>Fireproof:UL94-V0<br/>Current Max:5A<br/>Materials: PC+Copper<br/>Applications: 4 wires Direct connection<br/>Functions: Free wire soldering and wire skin peeling<br/>Wire: 18-22AWG ( Wire Size )</p>      |

|   |   |  |  |
|---|---|--|--|
|    | <p>Model: CL-L0041<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Fast Wire connected with strip light<br/>                     Width: 8mm<br/>                     CCT: Single color<br/>                     FPCB: Waterproof Strip+18-22AWG Wire</p> |    | <p>Model: CL-L0042<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Fast Wire connected with strip light<br/>                     Width: 8mm<br/>                     CCT: Single color<br/>                     FPCB: Waterproof Bareboard FPCB Strip + 18-22AWG Wire</p> |
|    | <p>Model: CL-L0043<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Strait Line connection with 2 Strip light<br/>                     Width: 8mm<br/>                     CCT: Single color<br/>                     FPCB: Dropping Glue/IP65</p>        |    | <p>Model: CL-L0044<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Strait Line connection with 2 Strip light<br/>                     Width: 8mm<br/>                     CCT: Single color<br/>                     FPCB: Bareboard FPCB</p>                             |
|   | <p>Model: CL-L0045<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Fast Wire connected with strip light<br/>                     Width:10mm<br/>                     CCT: Single color<br/>                     FPCB: Waterproof Strip+18-22AWG Wire</p> |   | <p>Model: CL-L0046<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Fast Wire connected with strip light<br/>                     Width:10mm<br/>                     CCT: Single color<br/>                     FPCB: Waterproof Bareboard FPCB Strip + 18-22AWG Wire</p> |
|  | <p>Model: CL-L0047<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Strait Line connection with 2 Strip light<br/>                     Width:10mm<br/>                     CCT: Single color<br/>                     FPCB: Dropping Glue/IP65</p>        |  | <p>Model: CL-L0048<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Strait Line connection with 2 Strip light<br/>                     Width:10mm<br/>                     CCT: Single color<br/>                     FPCB: Bareboard FPCB</p>                             |
|  | <p>Model: CL-L0049<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Fast Wire connected with strip light<br/>                     Width:10mm<br/>                     CCT: Single color<br/>                     FPCB: Waterproof Strip+18-22AWG Wire</p> |  | <p>Model: CL-L0050<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Fast Wire connected with strip light<br/>                     Width:10mm<br/>                     CCT: Single color<br/>                     FPCB: Waterproof Bareboard FPCB Strip + 18-22AWG Wire</p> |
|  | <p>Model: CL-L0051<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Strait Line connection with 2 Strip light<br/>                     Width:10mm<br/>                     CCT: Double color<br/>                     FPCB: Dropping Glue/IP65</p>        |  | <p>Model: CL-L0052<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Strait Line connection with 2 Strip light<br/>                     Width:10mm<br/>                     CCT: Single color<br/>                     FPCB: Bareboard FPCB</p>                             |

|   |  |  |   |
|---|--|--|---|
|    | <p>Model: CL-L0053<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Fast Wire connected with strip light<br/>                     Width:10mm<br/>                     CCT: RGB<br/>                     FPCB: Waterproof Strip+18-22AWG Wire</p>           |    | <p>Model: CL-L0054<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Fast Wire connected with strip light<br/>                     Width:10mm<br/>                     CCT: RGB<br/>                     FPCB: Waterproof Bareboard FPCB Strip + 18-22AWG Wire</p>   |
|    | <p>Model: CL-L0055<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Fast connection between 2 strip light<br/>                     Width:10mm<br/>                     CCT: RGB<br/>                     FPCB: Waterproof Strip+18-22AWG Wire</p>          |    | <p>Model: CL-L0056<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Fast connection between 2 strip light<br/>                     Width:10mm<br/>                     CCT: RGB<br/>                     FPCB: Waterproof Bareboard FPCB Strip +18-22AWG Wire</p>   |
|   | <p>Model: CL-L0057<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Fast Wire connected with strip light<br/>                     Width:12mm<br/>                     CCT: RGB+W<br/>                     FPCB: Waterproof Strip + 18-22AWG Wire</p>       |   | <p>Model: CL-L0058<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Fast Wire connected with strip light<br/>                     Width:12mm<br/>                     CCT: RGB+W<br/>                     FPCB: Waterproof Bareboard FPCB Strip +18-22AWG Wire</p>  |
|  | <p>Model: CL-L0059<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Fast connection between 2 strip light<br/>                     Width:12mm<br/>                     CCT: RGB+W<br/>                     FPCB: Waterproof Strip+18-22AWG Wire</p>        |  | <p>Model: CL-L0060<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Fast connection between 2 strip light<br/>                     Width:12mm<br/>                     CCT: RGB+W<br/>                     FPCB: Waterproof Bareboard FPCB Strip +18-22AWG Wire</p> |
|  | <p>Model: CL-L0061<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Fast Wire connected with strip light<br/>                     Width:10mm<br/>                     CCT: Single color<br/>                     灯板: Sleeveing LED strip+18-22AWG Wire</p> |  | <p>Model: CL-L0062<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Strait Line connection with 2 Strip light<br/>                     Width:10mm<br/>                     CCT: Single color<br/>                     FPCB: Sleeveing/IP67</p>                      |
|  | <p>Model: CL-L0063<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Fast Wire connected with strip light<br/>                     Width:10mm<br/>                     CCT: RGB<br/>                     灯板: Sleeveing LED strip+18-22AWG Wire</p>          |  | <p>Model: CL-L0064<br/>                     Name: Hippo Connector<br/>                     Fireproof:UL94-V0<br/>                     Current Max:5A<br/>                     Materials: PC+Copper<br/>                     Applications: Strait Line connection with 2 Strip light<br/>                     Width:10mm<br/>                     CCT: RGB<br/>                     FPCB: Sleeveing/IP67</p>                               |



Model: CL-L0065  
 Name: L Type 2 Pins Connectors  
 Fireproof:UL94-V0  
 Current Max:4A  
 Materials: PA66+Copper  
 Applications: Strait Line connection with 2 Strip light  
 Width:10mm  
 CCT: Single color  
 FPCB: Bareboard FPCB




Model: CL-D0001  
 Name: 1672 Double Layers insulated Conductor wires  
 Fireproof:VW-1  
 Current Max:2A  
 Materials: PVC+Copper




Model: CL-D0002  
 Name: 1672 Double Layers insulated Conductor wires  
 Fireproof: VW-1  
 Current Max: 2A  
 Materials: PVC+Copper




Model: CL-D0003  
 Name: 2464 Double Pins in 1 wire  
 Fireproof: VW-1  
 Current Max: 3A  
 Materials: PVC+Copper




Model: CL-D0004  
 Name: 2PIN Red&Black wires  
 Fireproof: VW-1  
 Current Max: 3A  
 Materials: PVC+Copper




Model: CL-D0005  
 Name: 3PIN outlet wire  
 Fireproof: VW-1  
 Current Max: 3A  
 Materials: PVC+Copper




Model: CL-D0006  
 Name: GRB outlet wire  
 Fireproof: VW-1  
 Current Max: 1.2A  
 Materials: PVC+Copper




Model: CL-D0007  
 Name: GRB outlet wire  
 Fireproof: VW-1  
 Current Max: 1.2A




Model: CL-D0008  
 Name: 6PIN outlet wire  
 Fireproof:VW-1  
 Current Max:1.2A  
 Materials: PVC+Copper















Model: CL-D0009  
 Name: Red&Black connecting wire  
 Fireproof:Connector 94-V0  
 Wire VW-1  
 Current Max:1.2A  
 Materials: Connectors PA66+Copper  
 Wire PVC+Copper  
 Applications: Fast connection between 2 strip light  
 Width: 8mm  
 CCT: Single color  
 FPCB: Bareboard FPCB(22AWG Wire)















Model: CL-D0010  
 Name: RGB Connecting wire  
 Fireproof:Connector 94-V0  
 Wire VW-1  
 Current Max:1.2A  
 Materials: Connectors PA66+Copper  
 Wire PVC+Copper  
 Applications: Fast connections between the controllers&Strip  
 Width:12mm  
 CCT: RGB  
 FPCB: Bareboard FPCB(22AWG Wire)



Model: CL-D0011  
 Name: Piercing connecting wires  
 Fireproof:Connector 94-V0  
 Wire VW-1  
 Current Max:1.2A  
 Materials: Connectors PA66+Copper  
 Wire PVC+Copper  
 Applications: Connected with the Controllers with Pins or the wires with pins  
 Width:12mm  
 CCT: RGB  
 FPCB: Bareboard FPCB(22AWG Wire)

|  |   |  |   |
|--|---|--|---|
|    | <p>Model: CL-D0012<br/>                     Name: Fresh New Piercing connecting wires<br/>                     Fireproof: Connector 94-V0<br/>                     Wire VW-1<br/>                     Current Max: 1.2A<br/>                     Materials: Connectors PA66+Copper<br/>                     Wire PVC+Copper<br/>                     Applications: Fast connections between the controllers &amp; Strip<br/>                     Width: 8mm<br/>                     CCT: Single color<br/>                     FPCB: Bareboard FPCB(22AWG Wire)</p>                            |    | <p>Model: CL-D0013<br/>                     Name: Fresh New Piercing connecting wires<br/>                     Fireproof: Connector 94-V0<br/>                     Wire VW-1<br/>                     Current Max: 1.2A<br/>                     Materials: Connectors PA66+Copper<br/>                     Wire PVC+Copper<br/>                     Applications: Connected with the Controllers with Pins or the wires with pins<br/>                     Width: 12mm<br/>                     CCT: RGB<br/>                     FPCB: Bareboard FPCB(22AWG Wire)</p> |
|    | <p>Model: CL-D0014<br/>                     Name: Fresh New Piercing connecting wires<br/>                     Fireproof: Connector 94-V0<br/>                     Wire VW-1<br/>                     Current Max: 1.2A<br/>                     Materials: Connectors PA66+Copper<br/>                     Wire PVC+Copper<br/>                     Applications: Connected with the LED strip with DC connectors or the strip with DC connectors<br/>                     Width: 8mm<br/>                     CCT: Single color<br/>                     FPCB: Bareboard FPCB(22AWG Wire)</p> |    | <p>Model: CL-D0015<br/>                     Name: Fresh New Piercing connecting wires<br/>                     Fireproof: Connector 94-V0<br/>                     Wire VW-1<br/>                     Current Max: 1.2A<br/>                     Materials: Connectors PA66+Copper<br/>                     Wire PVC+Copper<br/>                     Applications: Connection between 2 Strip light<br/>                     Width: 10mm<br/>                     CCT: Single color<br/>                     FPCB: Bareboard FPCB(22AWG Wire)</p>                       |
|   | <p>Model: CL-D0016<br/>                     Name: Old Piercing connecting wires<br/>                     Fireproof: Connector 94-V0<br/>                     Wire VW-1<br/>                     Current Max: 1.2A<br/>                     Materials: Connectors PA66+Copper<br/>                     Wire PVC+Copper<br/>                     Applications: Connection between 2 Strip light<br/>                     Width: 10mm<br/>                     CCT: Single color<br/>                     FPCB: Bareboard FPCB(22AWG Wire)</p>   |   | <p>Model: CL-D0017<br/>                     Name: Old Piercing connecting wires<br/>                     Fireproof: Connector 94-V0<br/>                     Wire VW-1<br/>                     Current Max: 1.2A<br/>                     Materials: Connectors PA66+Copper<br/>                     Wire PVC+Copper<br/>                     Applications: Connection between 2 Strip light<br/>                     Width: 10mm<br/>                     CCT: RGB<br/>                     FPCB: Bareboard FPCB(22AWG Wire)</p>                                      |
|  | <p>Model: CL-D0018<br/>                     Name: Old Piercing connecting wires<br/>                     Fireproof: Connector 94-V0<br/>                     Wire VW-1<br/>                     Current Max: 1.2A<br/>                     Materials: Connectors PA66+Copper<br/>                     Wire PVC+Copper<br/>                     Applications: Connection between 2 Strip light<br/>                     Width: 12mm<br/>                     CCT: RGB<br/>                     FPCB: Bareboard FPCB(22AWG Wire)</p>  |  | <p>Model: CL-D0019<br/>                     Name: Single color connectors free of soldering<br/>                     Fireproof: Connector 94-V0<br/>                     Wire VW-1<br/>                     Current Max: 1.2A<br/>                     Materials: Connectors PA66+Copper<br/>                     Wire PVC+Copper<br/>                     Applications: LED strip connection with Controller<br/>                     Width: 8mm<br/>                     CCT: Single color<br/>                     FPCB: Bareboard FPCB(22AWG Wire)</p>              |
|  | <p>Model: CL-D0020<br/>                     Name: Single color connectors free of soldering<br/>                     Fireproof: Connector 94-V0<br/>                     Wire VW-1<br/>                     Current Max: 1.2A<br/>                     Materials: Connectors PA66+Copper<br/>                     Wire PVC+Copper<br/>                     Applications: LED strip connection with Controller<br/>                     Width: 10mm<br/>                     CCT: Single color<br/>                     FPCB: Bareboard FPCB(22AWG Wire)</p>                                     |  | <p>Model: CL-D0021<br/>                     Name: RGB connecting wire free of soldering<br/>                     Fireproof: Connector 94-V0<br/>                     Wire VW-1<br/>                     Current Max: 1.2A<br/>                     Materials: Connectors PA66+Copper<br/>                     Wire PVC+Copper<br/>                     Applications: LED strip connection with Controller<br/>                     Width: 10mm<br/>                     CCT: RGB<br/>                     FPCB: Bareboard FPCB(22AWG Wire)</p>                          |
|  | <p>Model: CL-D0022<br/>                     Name: Both ends connecting wire free of soldering<br/>                     Fireproof: Connector 94-V0<br/>                     Wire VW-1<br/>                     Current Max: 1.2A<br/>                     Materials: Connectors PA66+Copper<br/>                     Wire PVC+Copper<br/>                     Applications: Connection between 2 Strip light<br/>                     Width: 8mm<br/>                     CCT: Single color<br/>                     FPCB: Bareboard FPCB(22AWG Wire)</p>  |  | <p>Model: CL-D0023<br/>                     Name: Both ends connecting wire free of soldering<br/>                     Fireproof: Connector 94-V0<br/>                     Wire VW-1<br/>                     Current Max: 1.2A<br/>                     Materials: Connectors PA66+Copper<br/>                     Wire PVC+Copper<br/>                     Applications: Connection between 2 Strip light<br/>                     Width: 10mm<br/>                     CCT: Single color<br/>                     FPCB: Bareboard FPCB(22AWG Wire)</p>               |

|  |   |  |  |
|--|---|--|--|
|    | <p>Model: CL-D0024<br/>                 Name: One end connecting wire free of soldering<br/>                 Fireproof: Connector 94-V0<br/>                 Wire VW-1<br/>                 Current Max: 1.2A<br/>                 Materials: Connectors PA66+Copper<br/>                 Wire PVC+Copper<br/>                 Applications: LED strip connection with Controller<br/>                 Width: 12mm<br/>                 CCT: RGB+W 灯带<br/>                 FPCB: Bareboard FPCB(22AWG Wire)</p> |    | <p>Model: CL-D0025<br/>                 Name: Waterproof Transparant DC connecting wire<br/>                 Fireproof: VW-1<br/>                 Current Max: 0.8A<br/>                 Materials: PVC+Copper</p>                         |
|    | <p>Model: CL-D0026<br/>                 Name: Waterproof Transparant DC connecting wire<br/>                 Fireproof: VW-1<br/>                 Current Max: 0.8A<br/>                 Materials: PVC+Copper</p>  |    | <p>Model: CL-D0027<br/>                 Name: 4Pin Female connecting wire<br/>                 Fireproof: VW-1<br/>                 Current Max: 0.8A<br/>                 Materials: PVC+Copper</p>                                       |
|   | <p>Model: CL-D0028<br/>                 Name: 4Pin Male connecting wire<br/>                 Fireproof: Connector 94-V0<br/>                 Wire VW-1<br/>                 Current Max: 0.8A<br/>                 Materials: PVC+Copper</p>  |   | <p>Model: CL-D0029<br/>                 Name: 1 for 2 Connecting wire<br/>                 Fireproof: Connector 94-V0<br/>                 Wire VW-1<br/>                 Current Max: 0.8A<br/>                 Materials: PVC+Copper</p> |
|  | <p>Model: CL-D0030<br/>                 Name: Waterproof Transparant Male connecting wire<br/>                 Fireproof: VW-1<br/>                 Current Max: 0.8A<br/>                 Materials: PVC+Copper</p>  |  | <p>Model: CL-D0031<br/>                 Name: Waterproof Transparant Female connecting wire<br/>                 Fireproof: VW-1<br/>                 Current Max: 0.8A<br/>                 Materials: PVC+Copper</p>                     |
|  | <p>Model: CL-D0032<br/>                 Name: DC Female Connecting wire<br/>                 Fireproof: VW-1<br/>                 Current Max: 1.2A<br/>                 Materials: PVC+Copper</p>  |  | <p>Model: CL-D0033<br/>                 Name: DC Male Connecting wire<br/>                 Fireproof: VW-1<br/>                 Current Max: 1.2A<br/>                 Materials: PVC+Copper</p>   |
|  | <p>Model: CL-D0034<br/>                 Name: DC Male&amp;Female Connecting wire<br/>                 Fireproof: VW-1<br/>                 Current Max: 0.8A<br/>                 Materials: PVC+Copper</p>   |  | <p>Model: CL-D0035<br/>                 Name: DC Male&amp;Female Connecting wire<br/>                 Fireproof: VW-1<br/>                 Current Max: 0.8A<br/>                 Materials: PVC+Copper</p>                                |





Model: CL-D0036  
 Name: 1 for 3 Connecting wire  
 Fireproof: VW-1  
 Current Max: 0.8A  
 Materials: PVC+Copper



Model: CL-D0037  
 Name: DC Male&Female Extending wire  
 Fireproof: VW-1  
 Current Max: 0.8A  
 Materials: PVC+Copper




Model: CL-D0038  
 Name: DC Male&Female Extending wire  
 Fireproof: VW-1  
 Current Max: 0.8A  
 Materials: PVC+Copper



Model: CL-D0039  
 Name: 1 for 2 Connecting wire  
 Fireproof: VW-1  
 Current Max: 0.8A  
 Materials: PVC+Copper




Model: CL-D0040  
 Name: 4Pin Male connecting wire  
 Fireproof: VW-1  
 Current Max: 1.2A  
 Materials: PVC+Copper



Model: CL-D0041  
 Name: DC Female Connecting wire  
 Fireproof: VW-1  
 Current Max: 1.2A  
 Materials: PVC+Copper



Model: CL-D0042  
 Name: DC Male Connecting wire  
 Fireproof: VW-1  
 Current Max: 1.2A  
 Materials: PVC+Copper



Model: CL-D0043  
 Name: DC Male&Female Extending wire  
 Fireproof: VW-1  
 Current Max: 1.2A  
 Materials: PVC+Copper



Model: CL-D0044  
 Name: 1 for 2 DC Male/Female connecting wire  
 Fireproof: VW-1  
 Current Max: 1.2A  
 Materials: PVC+Copper



Model: CL-D0045  
 Name: 5PIN Connecting wire  
 Fireproof: VW-1  
 Current Max: 1.2A  
 Materials: PVC+Copper



Model: CL-D0046  
 Name: 1 for 3 Connecting wire  
 Fireproof: VW-1  
 Current Max: 1.2A  
 Materials: PVC+Copper



Model: CL-D0047  
 Name: Both ends 4PIN Female Connecting wire  
 Fireproof: VW-1  
 Current Max: 1.2A  
 Materials: PVC+Copper

|  |  |  |  |
|--|--|--|--|
|    | <p>Model: CL-D0048<br/>                     Name: Both ends 4PIN Female Connecting wire<br/>                     Fireproof: VW-1<br/>                     Current Max: 1.2A<br/>                     Materials: PVC+Copper</p>   |    | <p>Model: CL-D0049<br/>                     Name: Both ends 4PIN Female Connecting wire<br/>                     Fireproof: VW-1<br/>                     Current Max: 1.2A<br/>                     Materials: PVC+Copper</p>   |
|    | <p>Model: CL-D0050<br/>                     Name: Both ends connecting wires<br/>                     Fireproof: Connector 94-V0<br/>                     Wire VW-1<br/>                     Current Max: 1.2A<br/>                     Materials: Connectors PA66+Copper<br/>                     Wire: PVC+Copper</p>  |    | <p>Model: CL-D0051<br/>                     Name: L901A-4 holes RGB Hub Box<br/>                     Fireproof: /<br/>                     Current Max: 1.2A<br/>                     Materials: Housing: PC<br/>                     Wire PVC+Copper</p>  |
|   | <p>Model: CL-D0052<br/>                     Name: L901A-4 holes RGB Hub Box<br/>                     Fireproof: /<br/>                     Current Max: 1.2A<br/>                     Materials: Housing: PC<br/>                     Wire PVC+Copper</p>  |   | <p>Model: CL-D0053<br/>                     Name: L822-4P Male Connecting wire<br/>                     Fireproof: Connector 94-V0<br/>                     Wire VW-1<br/>                     Current Max: 0.8A<br/>                     Materials: Connectors PA66+Copper<br/>                     Wire PVC+Copper</p>   |
|  | <p>Model: CL-D0054<br/>                     Name: L901A-9 holes RGB Hub Box<br/>                     Fireproof: /<br/>                     Current Max: 1.2A<br/>                     Materials: Housing: PC<br/>                     Wire PVC+Copper</p>  |  | <p>Model: CL-D0055<br/>                     Name: Single end 2PIN Connecting wire<br/>                     Fireproof: Connector 94-V0<br/>                     Wire VW-1<br/>                     Current Max: 1.2A<br/>                     Materials: Connectors PA66+Copper<br/>                     Wire PVC+Copper</p>  |
|  | <p>Model: CL-D0056<br/>                     Name: L803-12 holes Single Color Hub Box<br/>                     Fireproof: /<br/>                     Current Max: 1.2A<br/>                     Materials: Housing: PC<br/>                     Wire PVC+Copper</p>   |  | <p>Model: CL-D0057<br/>                     Name: On/Off Switches for testing Strip</p>  |
|  | <p>Model: CL-D0058<br/>                     Name: RGB Piercing connecting wires<br/>                     Fireproof: Connector 94-V0<br/>                     Wire VW-1<br/>                     Current Max: 1.2A<br/>                     Materials: Connectors PA66+Copper<br/>                     Wire PVC+Copper<br/>                     Applications: LED strip connection with Controller<br/>                     Width: 10mm<br/>                     CCT: RGB<br/>                     FPCB: Bareboard FPCB(22AWG Wire)</p> |  | <p>Model: CL-D0061<br/>                     Name: Both ends connecting wire free of soldering<br/>                     Fireproof: Connector 94-V0<br/>                     Wire VW-1<br/>                     Current Max: 1.2A<br/>                     Materials: Connectors PA66+Copper<br/>                     Wire PVC+Copper<br/>                     Applications: Connection between 2 Strip light<br/>                     Width: 12mm<br/>                     CCT: RGB+W<br/>                     FPCB: Bareboard FPCB(22AWG Wire)</p> |

|  |   |  |   |
|--|---|--|---|
|    | <p>Model: CL-B0023<br/>Name: Wire Fixed<br/>Fireproof:UL94-V0<br/>Materials: PA66</p>           |    | <p>Model: CL-B0024<br/>Name: Wire Fixed<br/>Fireproof:UL94-V0<br/>Materials: PA66</p>       |
|    | <p>Model: CL-B0026<br/>Name: Plastic Wire Fix<br/>Fireproof:UL94-V0<br/>Materials: Silicone</p> |    | <p>Model: CL-B0027<br/>Name: Plastic Wire Fix<br/>Fireproof:UL94-V0<br/>Materials: PA66</p> |
|   | <p>Model: CL-B0028<br/>Name: Plastic Wire Fix<br/>Fireproof:UL94-V0<br/>Materials: PVC+Iron</p> |   | <p>Model: CL-B0029<br/>Name: Silicone caps<br/>Fireproof:94-V0<br/>Materials: Silicone</p>  |
|  | <p>Model: CL-B0030<br/>Name: Silicone caps<br/>Fireproof:94-V0<br/>Materials: Silicone</p>      |  | <p>Model: CL-B0031<br/>Name: Silicone caps<br/>Fireproof:94-V0<br/>Materials: Silicone</p>  |
|  | <p>Model: CL-B0032<br/>Name: 3M Adhesive<br/>Fireproof: /</p>                                   |  | <p>Model: CL-B0080<br/>Name: Caps Silicone Glue<br/>Fireproof: /</p>                        |
|  |   |  |   |